



符合RoHS指令要求
CONFORM TO RoHS DNSTROCTIONS

A

A



特性 character	规格 specifications
1. 相数 Number of phase	2
2. 步 距 角 Step Angle	1.8°
3. 额定电压 Rated Voltage	DC 3.88V
4. 额定电流 Rated current	DC 0.67A
5. 保持转矩 Holding Torque	≥ 70mN.m
6. 相电阻 Winding resistance	5.8 \pm 10% ohm(20℃)
7. 相电感 Winding inductaoce	4.2 \pm 20% mH (1kHz)
8. 转向 (轴伸向看) Directlon of rotation	A-AB-B-CW
9. 转动惯量 Rotor Inertia	15 g.cm ²
10. 电机重量 Weight	0.22Kg
11. 绝缘等级 Insulation class	B Class

7. 相电感 Winding inductaoce	4.2±20% mH (1kHz)				UMot		视图 view				重庆优摩特科技有限公司 Chongqing UMot technology Co.Ltd.	
8. 转向（轴伸向看） Directlon of rotation	A-AB-B-CW						比例 inverse proportion		1：1			
9. 转动惯量 Rotor Inertia	15 g.cm²											
10. 电机重量 Weight	0.22Kg								A0			
11. 绝缘等级 Insulation class	B Class	标记 REV	修改内容 Description	日期 Date	设计 INSPECTED	审核 CHECKED	批准 APPROVED	日期 Date	版本 Version	型号 Model	28HS2401-28PG64JZS-300	

减速比：1:64

