


符合RoHS指令要求
CONFORM TO RoHS DNSTROCTIONS

A

A



特性 character	规格 specifications
1. 相数 Nunber of phase	2
2. 步 距 角 Step Angle	1.8°
3. 额定电压 Rated Voltage	DC 3.25V
4. 额定电流 Rated current	DC 0.5A
5. 保持转矩 Holding Torque	≥ 15mN.m
6. 相电阻 Winding resistance	6.5 $\pm 15\%$ ohm (20℃)
7. 相电感 Winding inductaoce	1.5 $\pm 20\%$ mH (1kHz)
8. 转向 (轴伸向看) Directlon of rotation	A-AB-B-CW
9. 转动惯量 Rotor Inertia	2 g.cm²
10. 电机重量 Weight	0.1Kg
11. 绝缘等级 Insulation class	B Class

减速比: 1:36

电气原理图
winding drawing

Winding diagram showing motor connections:

- A GRN
- C BLU
- M
- B BLK
- D RED

UMot				视图 view		重庆优摩特科技有限公司 Chongqing UMot technology Co.Ltd.			
				比例 inverse proportion	1:1				
				A0					
设计 INSPECTED	审核 CHECKED	批准 APPROVED	日期 Date	版本 Version	型号 Model	20HS1405-22PG36JZS-300			